

TECHNICAL DATA SHEET

Performance Characteristics

Property	Typical Value	Test Method*
Particles and Fibers LPC: ≥0.5 µm Fibers: >100 µm	12 x 10 ⁶ particles/m ² 800 fibers/m ²	1, TM22 2, TM22
Nonvolatile Residue IPA extractant DIW extractant	0.06 g/m ² 0.02 g/m ²	1, TM1 1, TM1
Ions Sodium Potassium Chloride	0.49 ppm 0.25 ppm 0.25 ppm	1, TM18 1, TM18 1, TM18

Physical Characteristics

Property	Typical Value	Test Method*
Absorbency Sorptive capacity Sorptive rate	330 mL/m ² 0.5 seconds	1, TM20 1, TM20
Basis Weight	120 g/m ²	1, TM20

***Test Methods**

- 1 – “Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments,” IEST-RP-CC004.3, Institute for Environmental Sciences and Technology, Rolling Meadows, IL, 2004; www.iest.org.
- 2 – E2090-12, “Standard Test Method for Size-Differentiated Counting of Particles and Fibers Released from Cleanroom Wipers Using Optical and Scanning Electron Microscopy,” ASTM International, West Conshohocken, PA, 2012; www.astm.org.
- TM – Refers to Texwipe Test Method – available upon request. Contact Texwipe Customer Service at www.texwipe.com or info@texwipe.com for a copy.

Note: The data in this table represent typical analyses.

Texwipe holds ISO 9001 and ISO 14001 registrations.

All Texwipe products conform to GHS classification for labeling (where applicable).

Shipping classification based on weight of inner package.

TexVantage™ Polyester Dry

TECHNICAL DATA SHEET



TexVantage™ Polyester
100% polyester

Products

Number	Description	Sterile	Packaging	Case
<i>Dry Wipers – TexVantage™ Polyester</i>				
TX8944	4" x 4" (10 cm x 10 cm) dry		300 wipers/bag (2 inner bags of 150)	20 bags
TX8949	9" x 9" (23 cm x 23 cm) dry		150 wipers/bag (2 inner bags of 75)	10 bags
TX8942	12" x 12" (31 cm x 31 cm) dry		100 wipers/bag	10 bags

TECHNICAL DATA SHEET

Description

TexVantage™ Polyester is made from 100% polyester with a sealed edge.

Available dry (TexVantage™).

Applications

- Wiping and cleaning surfaces, equipment and parts.
- Applying and removing lubricants, adhesives, residues and other solutions including disinfectants.
- Cleaning with solvents such as isopropyl alcohol (IPA), ethanol, acetone, and degreasers.
- Lining trays for holding, protecting, drying and storing of parts, equipment and devices.
- Appropriate for use with temperatures less than 400°F (205°C).

Industries

Aerospace	Animal Laboratory	Biologics
Cleanroom Design/Build	Compounding Pharmacies	Data Storage
Facilities Maintenance	Industrial	Laboratory
Medical Device	Microelectronics	Pharmaceutical
Printing/Graphics	Semiconductor	USP <797> / USP <800>

Features & Benefits

- Constructed from 100% polyester creating a wiper ideal for spill control, cleaning and solution application.
- Designed for use on abrasive surfaces. This wiper will not easily snag or abrade releasing particles and fibers into the process or environment.
- Excellent chemical resistance for compatibility with a variety of solutions.
- Meets USP <797> and USP <800> wiper requirements.
- Autoclave safe.
- Individually lot coded for ease of traceability and quality control.

Cleanroom Environment

- ISO Class 4 – 7
- Class 10 – 10,000
- EU Grade B – D

Shelf Life

- Non-Sterile (Dry) – 5 years from date of manufacture

Custom products available upon request.